

CASOL SYSTEMS PRIVATE LIMITED

FIRE ALARM & DETECTION SYSTEM - FIRE SPRINKLER BULB & FLEXIBLE HOSE AND WATER LEAK DETECTOR





FEATURES:

Wide range of bulb and fusible link sprinklers K Factor: 40, 57, 80, 115, (160,200 extended coverage only) Standard response, special response and quick response

Connection: 3/8" BSP. 1/2"NPT and 3/4" NPT

Finish: brass chrome, white

Deflector: pendant, upright, conventional, sidewall, and

concealed

CS-FS-B01/B02



CS-FH-H1.5/H2



FEATURES:

Reccessed escutcheons; adjustable 12.7mm or 19.1mm Flat escutcheons

Sprinkler cabinets; capacity for 6, 12, 24, 36 or 50 sprinklers

Sprinkler guards; for pendent and upright sprinklers Water shields; diameter 89mm, 100mm or 165mm Sprinkler wrenches for all sprinkler types Flexible hose, braided, unbraided





the signals sent by the sensor cables. In the event of any abnormal condition or

malfunction it activates an alarm that has to be acknowledged physically and reset.

Display: LCD for displaying status of all water leakage sensors, Door status. LED Display status for all zones Sensor Cables: Reliably senses any conductive fluid Non conductive and abrasion resistant polymers increase the strength of the cables.

