



# CASOL SYSTEMS PRIVATE LIMITED

## TIME ATTENDANCE - FACE+FINGERPRINT READER



**CS-FRT502**

### FUNCTIONS:

Identification methods include Face, Fingerprint/RFID Password, Elegant ergonomic design, 4.3" TFT touch screen is user-friendly and very intuitive 6 user-defined function keys, Contact relays for door access control (wires to door strike or 3rd party panel), Optional extendable scheduled-bell Infra-red optical system enables user-identification in poorly lit environments Optional built-in battery backup provides approx 4 hours continuous operation Optional built-in wireless Wi-Fi or GPRS for wireless communication Built-in contacts for 3rd party electric lock, door sensor, alarm, exit button, or bell. Wiegand Output for connections to 3rd party access control panels

### SPECIFICATIONS :

<b>Display</b>	<b>4.3" TFT Touch Screen</b>
<b>Face capacity</b>	<b>1200 (1:N)</b>
<b>Fingerprint capacity</b>	<b>2000</b>
<b>ID Card capacity</b>	<b>10,000</b>
<b>Logs capacity</b>	<b>1,00,000</b>
<b>Algorithm Version</b>	<b>ZKFace VX 7.0 &amp; ZKFinger VX10.0</b>
<b>Communication</b>	<b>TCP/IP, RS232/485</b>
<b>USB-HOST</b>	<b>Two USB-Host</b>
<b>Time attendance Standard functions</b>	<b>Automatic Status Switch, Self-Service Query, Work Code, T9 input, 9 digit user ID, DST, Photo-ID, Scheduled-Bell</b>
<b>Access control interfaces for</b>	<b>3rd Party Electric Lock, Door Sensor, Exit Button</b>
<b>Wiegand Signal</b>	<b>Output</b>
<b>Optional functions</b>	<b>ID/Mifare Card, SMS, GPRS, 3G, ADMS, Wi-Fi, 2000mAh backup battery</b>
<b>Power supply</b>	<b>DC 12V 3A</b>
<b>Verification Speed</b>	<b>2 sec</b>
<b>Operating temp</b>	<b>0 °C- 45 °C</b>
<b>Operating Humidity</b>	<b>20%-80%</b>
<b>Dimension(W×H×D)</b>	<b>193.6 * 146.8 * 111 mm</b>
<b>Gross Weight</b>	<b>1.49 kg</b>

“Haadhi Complex”, Second Floor, 15, Police Commissioner Office Road, Egmore, Chennai - 600 008.

Ph : 91 44 - 28192189 / 2199 Toll Free : 1800 121 4881

email : [casolsys@gmail.com](mailto:casolsys@gmail.com) [www.casolsystems.com](http://www.casolsystems.com)

Disclaimer: Specifications can be changed without prior notice.